




DALI/PUSH





Caractéristique produit :

- Tension : 220-240 V
- Fréquence : 50/60 Hz
- Température utilisation : -20 à +45°C
- Boîtier : plastique
- Gradable : oui

DIMM DALI/PUSH



DIMM 1-10V



- Dimensions : 123x79x30 mm
- Poids : 0.21 Kg



Référence	W	Tension de sortie	Courant de sortie	Tension de sortie max	IP	
8267311040	4-20W	12-58V	350mA	80V	IP20	
	5-23W		400mA			
	5-26W		450Ma			
	6-29W		500mA			
	7-32W		550mA			
	7-35W		600mA			
	8-38W	650mA				
	8-41W	700mA				
	9-42W	12-56V	750mA			
	10-45W		800mA			
	10-45W		12-53V			850mA
	11-45W		12-50V			900mA
	11-45W		12-47V			950mA
	12-45W		12-45V			1000mA
	13-45W	12-43V	1050mA			
	13-45W	12-41V	1100mA			

EN 61347-1:2015, EN 61347-2-13:2014+A1, EN 55015:2013+A1+A1, EN 61547:2009,
 EN 61000-3-2:2014, EN 61000-3-3:2013, EN 61000-4-11:2004, EN 61000-4-2:2009,
 EN 61000-4-3:2006+A1+A2, EN 61000-4-4:2012, EN 61000-4-5:2014, EN 61000-4-6:2014,
 EN 61000-4-8:2010