


Projecteur Flood LED Eco – IP65

Caractéristiques générales :

- 220-240V
- 50/60Hz
- SMD LED
- Facteur de puissance : 0.9
- IRC : 70+
- Durée de vie : L70 – 35000h
- T° de fonctionnement : -20/+40°C
- Fixation par lyre. Orientable à -45/+90°



H [m]	D [m]	10W		20W		30W		50W		70W		Beam Angle 110°	
		Max [lux]	Med [lux]	Max [lux]	Med [lux]	Max [lux]	Med [lux]	Max [lux]	Med [lux]	Max [lux]	Med [lux]		
1.50	3.93	150	46	324	110	445	138	701	217	966	299		
3.00	7.87	37	12	81	27	111	34	175	54	241	75		
4.50	11.80	17	5	36	12	49	15	78	24	107	33		
6.00	15.73	9	3	20	7	28	9	44	14	60	19		
7.50	19.67	6	2	13	4	18	6	28	9	39	12		

REF	[W]	[lm] LED	[lm] OUT	[lm/W] OUT	[K]	CRI	Beam Angle	AxBxH
8290164403	10	990	800	80	3000	70+	110°	120X130X45
8290164404	10	1050	850	85	4000	70+	110°	120X130X45
8290164406	10	1050	850	85	6000	70+	110°	120X130X45
8290264403	20	1900	1600	80	3000	70+	110°	155X170X55
8290264404	20	2020	1700	85	4000	70+	110°	155X170X55
8290264406	20	2020	1700	85	6000	70+	110°	155X170X55
8290364403	30	3300	2400	80	3000	70+	110°	195X205X65
8290364404	30	3450	2500	83	4000	70+	110°	195X205X65
8290364406	30	3450	2500	83	6000	70+	110°	195X205X65
8290564404	50	5300	4000	80	4000	70+	110°	195X205X65
8290564406	50	5300	4000	80	6000	70+	110°	195X205X65
8290764404	70	7300	5500	79	4000	70+	110°	235X245X80
8290764406	70	7300	5500	79	6000	70+	110°	235X245X80